

## NIGHT WALL SECURITY REVOLVING DOOR



Added security for revolving doors.

### Unique sliding drum wall

Bauporte now offer a unique security solution for our range of revolving doors. Our sliding drum wall eliminates the need for extra profiles and glazing to fabricate night closing screens. This also means our revolving doors look clean and sharp without the additional screens.

Constructed from welded stainless frames which are clad with stainless steel sheeting ensures even the most determined criminal will find it difficult to break through these doors.

The Bauporte NSWM security option is suitable for our Full Vision and Prestige range of doors. This means you still have all the benefits of these stylish doors, but with the added reassurance of a tested security door. Bauporte's NSWM system achieves security to EN 1627 and PAS24:2016 Annex B.

### TECHNICAL DATA.

<b>Product Reference:</b>	NSWM SECURITY REVOLVING DOORS
<b>Suitable Door Models:</b>	Circular Full Vision Circular Prestige Royal Full Vision Royal Prestige
<b>Material:</b>	Glass Stainless steel frame for added durability and strength Cladding 2mm Stainless Steel
<b>Number of wings:</b>	Three Wing Four Wing
<b>Operation:</b>	Fully Automatic Semi-automatic Manual
<b>Diameter:</b>	Circular-1800mm-3000mm. Available in 1mm increments Royal- 3000mm<. Available in 1mm increments
<b>Internal Height:</b>	2100mm – 9000mm<. Available in 1mm increments
<b>Clear Opening:</b>	720mm<* *Dependent on door model and configuration
<b>Locking:</b>	Special Bauporte Maglock

<b>Security Rating:</b>	RC2, RC3 and RC4 Complying with EN 1627-30 and PAS24:2016 Annex B.
<b>Canopy Prestige Doors:</b>	50mm<. Available in 1mm increments Please contact Bauporte for minimum heights if lighting or hot air units are required.
<b>Canopy Full Vision Doors:</b>	Laminated 18mm glass roof inside and out Exterior roof with stainless steel edging and two water drainage spouts
<b>Surface Finishes:</b>	Stainless Steel- With special Finishes on request
<b>Accessories:</b>	Matting Water Drainage Reservoir Heaters integrated into the mat well or canopy
<b>Push Bars:</b>	Vertical or Horizontal Handles are available
<b>Safety:</b>	Designed, Manufactured and installed to EN 16005
<b>Power Supply:</b>	230 V/50 Hz. Automatic and semi-automatic only.
<b>Drive Unit:</b>	Canopy installation, minimum canopy height 350mm Underfloor Drive Unit. (Pit size 1200 x 400x400mm (L x W x D) Automatic and semi-automatic only.)
<b>Warranties:</b>	Two Years or Lifetime with service contract* *Please contact Bauporte for further information
<b>Construction:</b>	Curved drum walls will be constructed from welded through stainless steel profiles, which are covered with 2mm stainless steel sheeting. <b>One fixed and one moving drum wall-</b> Glazed curved drum walls formed from clear curved P6B attack resistant laminated glass in one piece over the full height of the door and divided by the midstyle, width 110mm. Bottom glazing profile are 120mm, top profile is 50mm and end styles are 45mm width. Moving drum wall is manual or automatic locking into a special Bauporte profile achieving PAS24:2016 or RC2, 3, 4 security ratings. The rotating part will have three or four door leaves, constructed out of a welded through stainless steel, which will be clad with stainless steel sheets. In the center, there is a central post of Stainless steel connecting the top-part and bottom-part. Post diameter is 60mm. Glass: clear 12mm toughened glass. The profiles around each door panel are 27mm high. Door leaves are provided with double brushes on all edges.

[www.bauporte.com](http://www.bauporte.com)

BV Bauporte Design Entrances  
Zandsteen 14, 2132 MR Hoofddorp,  
Netherlands, Postbus 558,  
2130 AN Hoofddorp  
Tel: +31 (0)85 066 1203  
Sales: [sales@bauporte.com](mailto:sales@bauporte.com)

Bauporte Doors UK Ltd  
Office 212, Dowgate House,  
14-16 Dowgate Hill, London  
EC4R 2SU  
Tel: +44 (0)20 3411 5023  
Sales: [sales@bauporte.com](mailto:sales@bauporte.com)

Making an entrance 