

OPERATIONS & MAINTENANCE MANUAL

Date

PRODUCT DESCRIPTION

BALANCE PEDESTALS – Adjustable Height Pedestals with self-levelling headpiece for use with suspended paving, tiling and decking systems.

25 to 392 mm in height – injection moulded support pedestals made from virgin fibre Polypropylene (PP) with no fillers. Supplied with acoustic, anti slip shim fitretd to headpiece.

Packed into boxes of 25 units each. Weight tolerance per unit = 683kg.

PHYSICAL AND CHEMICAL PROPERTIES

MATERIAL	Virgin fibre injection moulded polypropylene	
WEIGHT TOLERANCE	683kg	
MAX TEMPERATURE	Plus 75 ° C	
MIN TEMPERATURE	Minus 40 °C	
BASE PLATE DIAMETER	200mm or 150mm	
HEADPIECE DIAMETER	120mm	
LUG WIDTH	2mm, 4mm or 6mm	
LUG HEIGHT	10mm or 20mm	
CODE	DESCRIPTION / SIZE	
SP-BAL-025-Z	25-50mm BALANCE Pedestal (with 2 extension plates)	
SP-BAL-047-Z	47-62mm BALANCE Pedestal	
SP-BAL-062-Z	62-82mm BALANCE Pedestal	
SP-BAL-077-Z	77-112mm BALANCE Pedestal	
SP-BAL-107-Z	107-142mm BALANCE Pedestal	
SP-BAL-137-Z	137-172mm BALANCE Pedestal	
SP-BAL-167-Z	167-202mm BALANCE Pedestal	
SP-BAL-197-Z	197-232mm BALANCE Pedestal	
SP-BAL-222-Z	222-257mm BALANCE Pedestal	
SP-BAL-252-Z	252-287mm BALANCE Pedestal	
SP-BAL-282-Z	282-317mm BALANCE Pedestal	
SP-BAL-312-Z	312-347mm BALANCE Pedestal	
SP-BAL-342-Z	342-377mm BALANCE Pedestal	
SP-BAL-EXTRA-097-Z	97-147mm BALANCE EXTRA Pedestal	
SP-BAL-EXTRA-137-Z	137-227mm BALANCE EXTRA Pedestal	
SP-BAL-EXTRA-222-Z	222-392mm BALANCE EXTRA Pedestal	

Fire classification	All Adjustable Pedestals are classified as "EUROCLASS E" according to EN 13501-1:2009 – Special Class B pedestals can be manufactured by special request	
Appearance	Black injection moulded pedestal Shim in black or yellow colour	
Odour	None	
pН	n/a	
Boiling point	n/a	
Softening point	>75°C	
Flash point	n/a	
Fire classification	EuroClass E	
Toxicity	These products are not classified as toxic	

PRODUCT LITERATURE

Included as Appendix A

PRODUCT INSTALLATION

To be used on predominantly flat decks. Units to be placed onto the structural decks, sufficiently strong to tolerate the weight of the system. Waterproofing membranes to be adequately protected before installation of units to prevent point loading and / or puncturing of membrane.

Pedestals are loose-laid without mechanical fixings or adhesive. Paving slabs, tiles or decking joists are placed onto headpieces and telescopic stems are twisted to alter the height of the pedestals so that the tiles / slabs / decking boards are flat and level in height.

Pedestals to be placed a maximum of 600mm apart.

MAINTENANCE DETAILS

Products are designed to be covered and not disturbed in the long-term. Cavities between the structural deck and the timber should be inspected at occasional intervals to ensure drainage channels do not become blocked and flammable material does not collect. Jets of water should be used to remove limited amounts of debris, taking care not to block up or damage drainage outlets. For large or compacted debris build-up, removal of the tiles / slabs / decking boards and removing the debris by hand or machine may be required.

HAZARDS IDENTIFICATION

The major hazards identified for these products are physical and include manual handling. Sparks may be generated from cutting processes.

FIRST-AID MEASURES

In event of cuts and damage from dropped timber, wash out wound with plenty of clean water. Seek medical attention

FIRE-FIGHTING MEASURES

These products do not constitute a fire hazard. Use extinguishing media appropriate to the surrounding fire conditions.

ACCIDENTAL RELEASE MEASURES

Damaged product can be taken up and disposed of to landfill as inert waste if necessary; however recycling is the preferred method of disposal. As supplied, the products are not classified as hazardous.

HANDLING AND STORAGE

When handling product, due regard should be paid to the risks outlined in the Manual Handling Operations Regulations 1992, appropriate PPE should be used. When cutting the product with a saw, appropriate measures to control dust should be used. The product should be stored in a safe and stable manner.

PERSONAL PROTECTIVE EQUIPMENT:

Wear suitable protective clothing e.g. overalls, gloves and safety boots to reduce the chances of physical injury while using this product.

Local Exhaust Ventilation, goggles and a dust mask to the relevant European standard (EN149) may be required if a cutting method that liberates dust is used.

ECOLOGICAL INFORMATION

Subsequent to manufacture, this is a stable product with no known adverse environmental effects.

DISPOSAL CONSIDERATIONS

Dispose of this product at any approved solid waste disposal site. Disposal of the product should be in accordance with any local or national regulations although recycling is preferred.

WARRANTIES

A limited warranty exists that the products will comply with the test data as laid out earlier in document. Warranty is limited to replacement of products which have been installed in the correct manner and for the correct purpose only. Warranty is limited to the value of the cost price of the materials only, not replacement costs or any other labour cost.

TRANSPORT INFORMATION

Classification for conveyance: - None required.

KEY CONTACTS

Wallbarn Ltd.

Unit 16 Capital Business Centre, 22 Carlton Road, South Croydon CR2 0BS

Tel: +44 (0)208 916 2222 Fax: +44 (0)208 916 2223

Email: sales@wallbarn.com
Web: www.wallbarn.com

APPENDIX A: WALLBARN PRODUCT BROCHURE

The following table summarizes the documents referenced in this document.

Document Name	Location
SUPPORT PADS FOR PAVING AND DECKING BROCHURE	https://www.wallbarn.com/pedestals-2/balance/
Wallbarn Ltd Terms & Conditions	https://www.wallbarn.com/terms-conditions-of-supply/